TEROS

PART NUMBER
CSM25BKTE1035S

CASE WITH POWER SUPPLY INCLUDED

TE-1035S

Mini Tower · Micro-ATX and Mini-ITX · 250 W ATX power supply

A MINI TOWER WITH REAL ROOM
Cards up to 26 cm and coolers up to 16 cm

Mini Tower with a 250 W ATX power supply already fitted and a rear fan installed. Unlike a typical small case, it takes graphics cards up to 26 cm and CPU coolers up to 16 cm. Micro-ATX and Mini-ITX boards, with 4 slots and four internal bays.



REFERENCE IMAGE

FORM FACTOR	POWER SUPPLY	GRAPHICS CARD	SLOTS
Mini Tower	250 W	Up to 26 cm	4

WHAT IT SOLVES

The small format that makes you give up nothing

Cards up to 26 cm

A dual-fan graphics card fits, with 16 cm of free height for the CPU cooler.

250 W power supply included

Fitted at the top, with a 24-pin main connector, 4-pin CPU, two SATA and two peripheral connectors.

Fan already fitted

An 80 mm rear fan comes from the factory, so the PC starts out ventilated without buying anything else.

Four drives

Two bays for 3.5" drives and two for 2.5" drives, enough for a work PC.

TEROS

PART NUMBER
CSM25BKTE1035S

The 26 cm of card length: many cases this size stop at 18 or 20 cm of usable length, which rules out almost every dual-fan card. Here 26 cm fit, plus 16 cm of height for the cooler, so the compact format no longer forces you to choose components by size.

WHERE IT DELIVERS

Built for small PCs that still have to perform

OFFICE AND HOME

Less width, less depth

16 cm wide and 29.3 cm deep: it fits beside the monitor or inside a cabinet, without the depth of a full tower.

- 38.2 x 16 x 29.3 cm
- 3.5 kg empty
- Micro-ATX and Mini-ITX

PCs WITH A DEDICATED CARD

Room for a real GPU

26 cm of length fits the most common dual-fan cards, and 16 cm of height allows a tower cooler.

- Card up to 26 cm
- Cooler up to 16 cm
- 4 expansion slots

BEFORE YOU BUILD

Which components fit

The included supply is 250 W: enough for a PC with integrated graphics or a low-power card, not for one that needs its own connector.

- 250 W power supply
- No extra PCIe connector
- 12-month warranty

DATASHEET · CASE

Structure, power supply and internal capacity

STRUCTURE

Case type	Standard · vertical tower
Form factor	Mini Tower
Supported boards	Micro-ATX · Mini-ITX
Expansion slots	4
Colour	Black

MATERIALS AND MEASUREMENTS

Chassis	SPCC steel, 0.7 / 0.8 mm
Front panel	ABS
Side and top panels	Metal
Dimensions	38.20 x 16.00 x 29.30 cm (H x W x D)
Net / gross weight	3.50 kg / 3.85 kg

POWER SUPPLY INCLUDED

Format and position	ATX · top-mounted
Power	250 W
Input voltage	115 V AC / 230 V AC
Connectors	1 x 24-pin · 1 x 4-pin 12 V · 2 x SATA · 2 x peripheral

STORAGE AND LIMITS

Internal bays	2 x 3.5" · 2 x 2.5"
Graphics card	Up to 26.00 cm
CPU cooler	Up to 16.00 cm high

FRONT PANEL

Front ports	1 x USB 3.0 · 2 x USB 2.0 · audio
Buttons and LEDs	Power and reset
Pre-installed fan	1 x 80 mm rear

WARRANTY
12 months
* TEROS products only · new product (NV)

POWER SUPPLY INCLUDED
250 W · ATX
Top-mounted · 80 mm rear fan included

COMPATIBILITY
MICRO-ATX · MINI-ITX
4 slots · card up to 26 cm · cooler up to 16 cm

For more information or project advice, contact your authorized distributor.

Images are for reference only. Warranty: 12 months * TEROS products only. TEROS® is a registered trademark.