TEROS

PART NUMBER
CSS35BKTE1040CS

SLIM CASE WITH POWER SUPPLY INCLUDED

TE-1040CS

Vertical SFF · 10.2 cm wide · 350 W TFX power supply

350 W TFX POWER SUPPLY
More power than a slim case usually brings

Compact vertical case 10.2 cm wide with a 350 W TFX power supply already fitted. It takes Micro-ATX and Mini-ITX boards, with 4 slots, four storage bays and USB-C and USB 3.0 ports at the front.



AN OFFICE COMPACT, WITH USB-C AT THE FRONT

REFERENCE IMAGE

WIDTH	POWER SUPPLY	GRAPHICS CARD	SLOTS
10.2 cm	350 W TFX	Up to 19.5 cm	4

WHAT IT SOLVES

Narrow, with more power supply than usual

350 W TFX power supply

A hundred watts more than the usual supply in a compact case, with 100 to 240 V input.

10.2 cm wide

Narrow vertical format: it takes little desk space and fits beside the monitor or inside a cabinet.

USB-C at the front

USB-C and USB 3.0 ports on the front panel, for the peripherals and drives that already use that connector.

Four bays

Two external, 5.25" and 3.5", and two internal, 3.5" and 2.5": room for an optical drive and two disks.

TEROS

PART NUMBER
CSS35BKTE1040CS

The 350 W TFX power supply: TFX is the long, narrow format used by slim cases, where a standard ATX supply does not fit. The 350 W give headroom over the usual 250 W of the segment: enough for a second drive, an optical drive and a low-power graphics card.

WHERE IT DELIVERS

Built for offices where the desk rules

OFFICES AND NEW DESKS

Small and tidy

Ten centimetres wide in a vertical format: it fits beside the monitor, inside the cabinet or under the counter.

- 33.8 x 10.2 x 35.6 cm
- 3.1 kg empty
- Micro-ATX and Mini-ITX

PCs WITH NEW PERIPHERALS

USB-C without adapters

The front panel already has USB-C as well as USB 3.0, so today's drives and accessories plug straight in.

- USB-C at the front
- USB 3.0 Type-A
- Audio output

BEFORE YOU BUILD

Which components fit

The compact format sets three measurements to check before quoting the PC's components.

- Card up to 19.5 cm
- Cooler up to 8 cm
- Power supply up to 17.5 cm

DATASHEET · CASE

Structure, power supply and internal capacity

STRUCTURE AND MEASUREMENTS

Form factor	SFF · vertical orientation
Supported boards	Micro-ATX · Mini-ITX
Expansion slots	4
Dimensions	33.80 x 10.20 x 35.60 cm (H x W x D)
Weight	3.10 kg
Colour	Black

FRONT AND VENTILATION

Front ports	USB-C (3.1 Gen 2) · USB 3.0 Type-A · audio
Button	Power
Radiator mount	Top · 240 mm

POWER SUPPLY INCLUDED

Format	TFX
Power	350 W
Input voltage	100 – 240 V AC · 50/60 Hz
Connectors	1 x 24-pin · 1 x 4-pin 12 V · 1 x SATA · 2 x peripheral

STORAGE AND LIMITS

External bays	1 x 5.25" · 1 x 3.5"
Internal bays	1 x 3.5" · 1 x 2.5"
Graphics card	Up to 19.50 cm
CPU cooler	Up to 8.00 cm high
Power supply length	Up to 17.50 cm

WARRANTY
12 months
* TEROS products only · new product (NV)

POWER SUPPLY INCLUDED
350 W · TFX
Fitted · 100 to 240 V input

COMPATIBILITY
MICRO-ATX · MINI-ITX
4 slots · card up to 19.5 cm · cooler up to 8 cm

For more information or project advice, contact your authorized distributor.

Images are for reference only. Warranty: 12 months * TEROS products only. TEROS® is a registered trademark.